

## Continuously Variable Transmission (CVT) Application Chart

For Support or Questions Please Contact Our Tech Services: 800-255-8138, Option 4

OEM	Specification	Suitable for Use	CVT Type	Transmission Supplier
Audi/VW	TL 52180, TL 52516	YES	Chain	Volkswagen
BMW	EZL 799A	YES	Belt	ZF, Punch
Daihatsu	Ammix CVTF-DC, Ammix CVTF-DFE	YES	Belt	Aisin
FCA	CVTF+4	YES	Belt	Jatco
Ford	WSS-M2C933-A, Ford MERCON C	YES	Chain	Ford
	Ford M2C928-A	YES	Belt	ZF
GM	DEX-CVT	YES	Belt	GM
	GM CVT	YES	Belt	Jatco
Honda	Honda Genuine CVT Fluid / Multi Matic Fluid (HMMF)	YES	Belt	Honda
	Honda HCF-2	YES	Belt	Honda
Hyundai / Kia	SP CVT-1	YES	Belt	Hyundai
Mazda	CVTF 3320	YES	Belt	Aisin
Mercedes Benz	MB-Approval 236.20	YES	Belt	Daimler
Mitsubishi	Dia Queen CVTF J1, Dia Queen CVTF J4, Diamond ATF SP III	YES	Belt	Jatco
Nissan*	NS-1, NS-2, NS-3	YES	Belt	Jatco
Subaru	Subaru e-CVTF	YES	Belt	Jatco
	Lineartronic CV-30, Lineatronic CVTF-II, High torque CVTF	YES	Chain	Fuji Heavy
Suzuki	CVT Fluid Green1, CVT Fluid Green2	YES	Belt	Jatco
	Suzuki CVTF 3320	YES	Belt	Aisin
Toyota	TC, FE	YES	Belt	Toyota; Aisin
	Toyota WS	YES	Hybrid	Aisin
Subaru	Subaru i-CVT F	YES	Belt	Fuji Heavy
	Subaru i-CVT FG	YES	LT. TK	Fuji Heavy

\*Nissan Matic W: See Automatic Transmission Fluid (ATF) Application Chart.

### Applicable to the Following Full Throttle Products:

Description	Product #	Net Weight
CONTINUOUSLY VARIABLE TRANSMISSION (CVT) FLUID	FT10603	1 Gal (3.78 mL)